



CASE IH FARMALL B

Hard-working, compact, and extremely versatile.

Thanks to smart design, rugged construction and reliable horsepower, all 3 and 4 cylinder diesel engines provide horsepower ranging from 23 to 57, so be sure you'll have a machine that works as hard as you do. you're sure to find a model that fits the needs of your operation. These tractors feature gear or hydrostatic transmissions, a comfortable operator seat with ergonomic controls and a range of front end loader options.

So whether you put one of these tractors to work on a dairy farm, livestock Farmall B Series tractors deliver tonnes of performance in a compact size. Their operation, small farm, or need it for groundskeeping and landscaping, you can

CASE IH FARMALL. THE PROVEN PERFORMER.



FARMALL 20B & 25B

Performance and agility combined in a powerful, small-chassis compact tractor.

With its proven three cylinder, high torque diesel engine and easy to operate two-range hydrostatic transmission, these purpose built compact tractors are perfect for pulling trailers and light implements, mowing and front loader work.

MODELS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	DRY WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 20B	3 cylinder diesel	1.21	23 (17)	64 Nm	25 litres	650kg	720kg	PLc05	Standard or 4-in-1	1.85m	200kg
Farmall 25B	3 cylinder diesel	1.32	27 (20)	79 Nm	25 litres	650kg	730kg	PLc05	Standard or 4-in-1	1.85m	200kg



MODERN STYLISH DESIGN

Stylish & compact design is optimal for small farm or house operation

ENGINE

Fuel efficient engine delivers quiet, reliable performance

LARGE FUEL TANK

25L capacity provides long operation times

ERGONOMICALLY DESIGNED CONTROL SYSTEM

Easily accessible for maximum comfort and convenience

STANDARD MID PTO

2000 RPM Mid PTO for optional height adjustable 60" mid-mount mower that produces a smooth and beautiful cut

HYDROSTATIC TRANSMISSION

Maximises ease of use with effortless, clutch-less and instant speed and directional changes with a simple push of the pedals



FARMALL 35B

The mighty 38 hp helper.

FOR THE SERIOUS LIFESTYLE FARMER

With its fuel efficient 4-cylinder engine and 1,385kg dry weight, the Farmall 35B takes lifestyle farming to a whole new level. With a host of standard features normally found on larger tractors, it's no wonder the Farmall 35B is the most popular model in the Case IH lifestyle range.

MODELS	TRANSMISSION	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 35B	Hydrostatic/ Mechanical	4 cylinder diesel	1.76	38 (28)	103 Nm	33 litres	820kg	Mech 1385kg / Hydro 1403kg	PLc10	Standard or 4-in-1	2.45m	375kg

MODELS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	DRY WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 40B	4 cylinder diesel	2.5	41 (30)	130 Nm	36 litres	1252kg	1620kg	PLc15	Standard or 4-in-1	2.7m	420kg
Farmall 50B	4 cylinder diesel	2.5	47 (35)	140 Nm	36 litres	1252kg	Mech 1650kg / Hydro 1680kg	PLc15	Standard or 4-in-1	2.7m	420kg

FARMALL 40B & 50B

The professional's choice



2.5L four cylinder diesel power matched with either a three range hydro or 16x16 synchro transmission means you're always prepared for the toughest challenge. Choose from ag, turf, or industrial tyre options.

STANDARD EQUIPMENT

- Dry type air cleaner
- Hand and foot throttle control
- Adjustable seat
- ROPS with seat belt
- Instrumentation : Alternator
- Warning light, engine oil pressure light
- Gauges : water, fuel, tachometer with hour meter
- Hydraulic position control
- Turn signals

ADJUSTABLE SEAT

Fully adjustable seat offers comfortable working condition during long operation

POWERFUL 3-POINT HITCH

The powerful 3-point hitch lift capacity of 1,830kg allows usage of a wide variety of implements

DASH PANEL

All of the important functional data is yours at a glance to keep you in better control of your tractor





STANDARD EQUIPMENT

- Dry type air cleaner
- Hand and foot throttle control
- Instrumentation : Alternator
- Warning light, engine oil pressure light
- Gauges : water, fuel, tachometer w/ hour meter
- Hydraulic draft and position control
- Front outlet valve and loader joystick
- Automatic lift arm
- Rear working light
- Adjustable seat
- ROPS with seat belt
- Turn signals
- Telescopic stabilizer & drawbar



FARMALL 60B

The perfect all-rounder. Available in Cab or ROPS.

TO TACKLE THE BIG JOBS

The Farmall 60B is the heavyweight of the Case IH lifestyle range. Its turbocharged engine delivers effortless power – and an array of impressive features such as two sets of hydraulic remotes and three-speed PTO are fitted as standard.

OPTIONAL EQUIPMENT

■ Front bumper & weight

ADDITIONAL EQUIPMENT ON CABIN MODELS

- Deluxe Cabin with Heating and A/C
- Deluxe Stereo system with CD Player

LARGE CAPACITY AIR CLEANER

This not only has a higher air purification capacity, it also makes maintenance easier thanks to the longer filter use period

DASH PANEL

better control of your tractor

FULL FLAT DECK

Full flat deck and rubber mat ensure user-friendly working condition

AUDIO SYSTEM / AIR-CONDITIONER (CABIN MODEL ONLY)

Internal speaker and CD/Radio system installed standard and high quality air-conditioner makes pleasant work time

DELUXE ADJUSTABLE SEAT WITH RETRACTABLE SEAT BELT

All of the important functional data is yours at a glance to keep you in Keeps you safe and comfortable even during long operations

MODELS	TYPE	SIZE	HP (KW)	TORQUE	FUEL TANK	REAR LIFT CAPACITY	WEIGHT	FRONT END LOADER	BUCKET TYPE	MAX LIFT HEIGHT	LIFT CAPACITY
Farmall 60B	4 cylinder diesel	2.5 L	57 (43)	170 Nm	80 litres	1850kg	Cab 2370kg/ROPS 2165kg	PLc25	Standard or 4-in-1	2.9m	810kg ROPS/ 725kg Cab



SYSTEMS APPROACH

When you buy a Case IH machine, you can be sure not only that you're buying the best product, but also that you've got the best dealer back-up behind you. Case IH dealers can offer advice on selecting and financing the right machine, will ensure they deliver what you need when you need it, and will then continue to back you and your equipment with the service and spare parts backing you'd expect from a name as trusted as Case IH.



IT'S LIKE HAVING A PARTNER BESIDE YOU ALL SEASON.

Case IH has more professionals in the field working alongside producers than anyone else – two out of three Case IH employees work right where you do.

Case IH dealers have the know-how to help you manage your equipment investment to get the most out of every dollar. Our parts and service technicians have the skills and expertise it takes to maintain your equipment and keep it operating at peak performance. And CNH Capital can work with you to customise financing solutions that fit your unique needs. It's an entire system with only one goal in mind – to keep you up and running, working the way you want.



OFFERING FINANCIAL SOLUTIONS FOR MORE THAN 50 YEARS.

CNH Industrial Capital's extensive experience in the agricultural industry has created a deep understanding of your unique needs. Competitive equipment financing with flexible payments can be timed to your cash flow. Or, conserve capital and reduce upfront payments with operating lease options. For other needs, choose from commercial revolving accounts specific to the agricultural industry. We can even help you protect your equipment investment with a wide variety of insurance and equipment protection products. There are financing options that fit the way you farm. CNH Industrial Capital helps you find them.

FARMALL B SERIES TRACTOR SPECIFICATIO	NS							
RACTOR MODEL	20B	25B	35B	40B	50B	60B		
NGINE								
iross HP (kW)	23(17)	27(20)	38(28)	41(30)	47(35)	57(43)		
Max Torque (Nm)	64 79		103	1 1		170		
spiration			Natural		'	Turbo		
ylinders	3	3	4	4	4	4		
Displacement	1.125	1.318	1.758	2.505	2.505	2.505		
ated Speed (RPM)		2700	'					
uel tank capacity (Ltr)		25	33		36	80		
TO								
ated PTO Power HP (kW)	16.5(12.1)	20(14.7)	29(22) - Hydro 31(23) - Mech	34(25)	37(27) - Hydro 39(29) - Mech	47(35)		
TO Speed			540		, , , , , , , , , , , , , , , , , , ,	540/750/1000		
TO Type			Electro-Hydraulio	c Independent				
RANSMISSION			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,					
lechanical								
anges	N/A	N/A	12 x 12	16 x 16	16 x 16	16 x 16		
peed Range (kph)	N/A	N/A	1.2 - 24	1.2 - 27	1.2 - 27	1.2 - 32		
lydrostatic		14/1	216 61	1.E L/		1.2 02		
anges	2 2		3	N/A	3	N/A		
peed Range (kph)	0 - 15.7	0 - 15.7	0 - 25	N/A	0 - 25	N/A		
LECTRICAL SYSTEM	0 13.7	0 10.7	0 20	14//	0 23	1077		
ystem Voltage (v)			12	<u> </u>				
Iternator rating (A)			50ar					
attery (CCA)	60	0AH	3041	80AH		100AH		
YDRAULIC SYSTEM	0.0	OALL		OOAII		IOOAII		
			Gear P	umn				
/pe		10	30	шпр	29	36		
apacity - excludes steering and trans (I/min)		1		1 rear + joystick and 4 front outlets				
emotes (std)		1		rear + joystick and 4 from ou	liets	2 Front/2Rear		
point Linkage Category		650	Cat. 1 820	Cat. 2 1850				
Point Linkage Capacity @ Ball Ends (kg)	- 6	550		820 1252 Hydrostatic				
teering			пуигоз	SIGUC				
IMENSIONS	700	700	1400 11 1 1005 14 1	1500	1600 11 1 1650 14 1	DODO 0165 0 1 007		
Approximate Shipping Weight - (kg)	720	730	1403 - Hydro 1385 - Mech.	1620	1680 - Hydro 1650 - Mech.	ROPS - 2165 Cab - 237		
Ground Clearance - Under Drawbar (mm)	290	290	300	372	372	407		
/heelbase (mm)		500	1674	1758		2047		
Overall Length (mm)		660	2987	3192		3556		
Overall Width (mm)		226	1333	1672		1700		
Overall Height (mm)		370	2352	2416 2447		2650 - ROPS 2465 - Ca		
urning Radius without Brakes (m)	2.62	2.62	3.05	3.08	3.08	3.3		
Indicative only – Will vary depending on specification & who	eei equipment.							
					PLC15			
OADER MODEL (PRIME LIFT COMPACT)		.C05	PLC10		PLC25			
Lift Height (pivot pin)	1850mm		2450mm	2703mm 420kg		2900mm		
ated Operating Load - STD Bucket/Loader/Tractor		00kg	375kg		810kg ROPS/725kg Ca			
pader Lift Capacity kg - Max (Loader Only)		95kg	693kg		1131kg			
ucket Width mm (inches)		0 (52)	1500 (59)	to	to 1860 (73)			
ounterweight Recommendation	23	30kg	245kg		350kg	810kg ROPS/725kg Ca		

^{*}Indicative only – Will vary depending on specification & wheel equipment.

 $0 \mid$



SAFETY NEVER HURTS!TM Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial Australia Pty Ltd reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used. ©2016 CNH Industrial Australia Pty Ltd. All rights reserved. Case IH, its respective logos and the red, black and grey color scheme, as well as corporate and product identity used herein, are trademarks of CNH Industrial N.V. and may not be used without permission. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Printed in Australia. www.caseih.com 17AUSFAR003

